



< VIDEO WALL >



- Fácil instalación



- Conectividad



- Bajo consumo



- Alta resolución



- Impacto visual



- Alto brillo

DESCRIPCIÓN

Con un bisel (marco) espectacularmente estrecho, de tan solo 1.7mm, sumando ambos marcos, estas pantallas son ideales para formar parte de un video wall LCD prácticamente perfecto. Este marco tan estrecho ofrece una imagen de gran calidad y hace que su ojo se centre en el contenido de la pantalla.

En los paneles Premium de vídeo Wall, el brillo y el contraste está mejorado cuando se compara con un panel LCD regular. La técnica de S-PVA garantiza la visibilidad en 178 °

Puede actualizar su pantalla para conectarse en red, lo que le permite actualizar de forma remota la pantalla a través de LAN, Wi-Fi o 4G



ESPECIFICACIONES

Item NO		INS-IVM 46	INS-IVM 49	INS-IVM 55
Panel	Size	46inch	49inch	55inch
	Panel Type	a-Si TFT-LCD,	a-Si TFT-LCD,	a-Si TFT-LCD,
	Screen Size	46 inch	46inch	55 inch
	Resolution	1920*1080		
	Bezel	5.5mm (3.5mm / 1.8mm / 0mm)		
	Brightness	500cd		
	Contrast Ratio	3500:1 (Typ.) **	3000:1 (Typ.) **	4000:1 (Typ.) **
	Response Time	8 (Typ.)(G to G)		
	Viewing Angle	178/178 (Typ.)(CR > 10)		
	Display Area	1018.08×572.67 mm	1073.8604mm	1209.6×680.4 mm
Colour	16.7M			
Input/Output Port	1 channel CVBS, interface is BNC, carrier, support PAL/NTSC full system, 1 channel VCA, support VGA signal 1920×1080 60Hz below most 60Hz resolution, 1 channel DVI, support DVI signal below 3840×2160P 30Hz signal Resolution, 1 channel HDMI, support HDMI 3840×2160p 60Hz signal resolution below, 1 channel DP, support resolution below 3840×2160p 30Hz signal, 1 channel USB, program upgrade, 1 channel RJ45, RS232 control signal loop-in port, infrared access conversion interface (interface type is RJ45), 2 way RJ45, RS232 control signal loop-out port			
Video Features	Display Type	Normal, Soft, Users, Dynamic		
		3D digital comb filter, 3D image noise reduction, 3D motion adaptive comb filter, etc.		
Language	Multi language (Optional)			
Power	Input Voltage	AC100 V ~ 240 V, 50-60 Hz		
	Power Consumption(Watt)	< 220W		
	Standby(Watt)	< 1W		
Environment	Working Temperature (°C)	0°C ~ 40°C		
	Storage Humidity	-20°C ~ 55°C		
	Working Humidity	20% ~ 80%		
Others	Video Wall Size	1024x78.6x124.2 (mm)	1075.7x605.9x109.1(mm)	1213.5x684.3x115.1(mm)
	Video Wall Weight	23 kg	24 kg	28
	Package Size	1126x686x330mm	1160x700x330mm	1310x800x300mm

INSTALACIÓN

